COOKWARE (PTFE)



ILACOLOR SP-100

Good one or two-coat system for exterior applications. This exterior coating is available in many decorative colours. Special colour effects are only available as a two-coat system.

- Exterior coating based on silicone polyester
- Good cleanability
- Adequate stain resistance
- Special colour effects only as a two-coat system

Properties

Number of layers 1 - 2

Coating thickness $15 - 20 \mu m / 0.59 - 0.79$

mils

Curing temperature

to approx

280 °C / 536 °F

Service temperature 250 °C / 482 °F

Staining resistance ★ ★ ★ ★

Application

| Application | |
|------------------|----------------|
| Defrosting plate | ~ ~ ~ ~ |

Substrate

| Substrate | Pre-treatment | Suitability |
|-------------------------|----------------------------|--------------|
| pressed / forged alu | sandblasting with corundum | / / / |
| alu cast | sandblasting with corundum | / / / |
| stainless steel | sandblasting with corundum | 4 4 4 |

COOKWARE (PTFE)



Cleaning and care instructions

Wipe the outside of the cookware with a wet cloth. For stubborn stains, clean the pan under hot water, a mild washing-up liquid and the fine side of a dishwashing sponge or a soft dishwashing brush. We strongly advise against using cleaning metal sponges. Always wipe the pan dry before storing it.

Coated pans can be cleaned in the dishwasher, although this is not recommended due to the aggressive cleaning agents. Cleaning by hand is preferable.