

DURIT® HL

Premium technology PTFE system

- Easy to use
- Durable and superior non-stick performance
- Very high DFT are achievable
- Very good corrosion resistance



DURIT® HL

Product specification

Characteristics	
Material base	PTFE modified
Number of layers	2
Kind of application	conventional spraying
Recommended DFT (1)	35-70 µm
Performance profile	
Non-stick effect	★★★★
Low friction properties	★★★★★
Corrosion resistance	★★★★★
Acid resistance	★★★★
Alkaline resistance	★★★★

(1) DFT = to the layer itself, it's not of the total system

Applications			
Baguettes	Burger buns, Hot dogs, Sandwich, Toast, Rusks	Bretzel	Sweet fat products
			
✓ ✓ ✓	✗	✗	✓ ✓
Sweet pastry	Cakes	Salt dough	Ciabatta
			
✓ ✓	✓ ✓	✓	✓ ✓
Pain au lait	Madeleines	Protein in sugar	Pre-frozen
			
✗	✗	✗	✓

✓ ✓ ✓ First choice | ✓ ✓ Recommended | ✓ Possible after consolidation | ✗ NOT recommended

These data are based on the experience and the test results that are available to us. Because of the variety of application possibilities, we give these processing instructions without obligation. This information sheet does not replace the application guide (technical data sheet) of the specific product.