

DURIT® Professional X-500

High Build and coloured FEP dispersion

- Range of low, mid and high build choices available
- Increased permeation resistance
- Suitable for robotic or manual application



DURIT® Professional X-500

Product specification

Characteristics	
Material base	FEP
Number of layers	2 or more
Kind of application	conventional spraying
Recommended DFT (1)	15-25 µm
Performance profile	
Non-stick effect	★★★★
Low friction properties	★★★
Corrosion resistance	★★★★
Acid resistance	★★★
Alkaline resistance	★★★

(1) DFT = to the layer itself, it's not of the total system

Applications			
Baguettes 	Burger buns, Hot dogs, Sandwich, Toast, Rusks 	Bretzel 	Sweet fat products 
✓	✓	✗	✓ ✓
Sweet pastry 	Cakes 	Salt dough 	Ciabatta 
✓ ✓	✓ ✓	✗	✗
Pain au lait 	Madeleines 	Protein in sugar 	Pre-frozen 
✓	✗	✓	✗

✓✓✓ First choice | ✓✓ Recommended | ✓ Possible after consolidation | ✗ NOT recommended

These data are based on the experience and the test results that are available to us. Because of the variety of application possibilities, we give these processing instructions without obligation. This information sheet does not replace the application guide (technical data sheet) of the specific product.